

SUB WOOFER

ES 250D.5 750W



Technical Specifications

Component	Subwoofer	
Size	mm (in.)	250 (10)
Power handling W	peak	750
	cont. program	250
Impedance	Ω	4 + 4
Frequency response	Hz	28 ÷ 300
Sensitivity	dB/SPL	92
Magnet size D x d x h	mm (in.)	120 x 60 x 34 (5.7 x 2.35 x 1.34)
	l (cu.in)	0,65 (39.6)
Total Driver Displacement		
Voice Coil \varnothing	mm (in.)	50 (2)
Magnet	High density flux ferrite	
Cone	Water repellent pressed paper	
Weight of one component	kg (lb.)	4 (8.82)
*X-mech	mm (in.)	15 (0.59)

*X-mech, maximum mechanical excursion: it indicates the motion range in the speaker linear functioning area, in both ways.

1. V-cone® technology with water-repellent paper membrane, for reduced moving assembly mass and increased sensitivity.
2. Wide-wave spider profile, for high mechanical resistance against impulsive stresses; its resin-bonded fibre ensures consistent electro-acoustic parameters in time.
3. High density foam surround, for extreme mechanical and acoustical linearity, even under high excursion.
4. Copper voice coil wound on aluminium former, combined with the spider support cooling system and bottom plate vent holes, for outstanding thermal capacity in power peaks.
5. Silver plated silicone shielded lead wires ending with tin-plated, high current terminals, for high resistance against mechanical stress and low contact resistance.
6. Dual voice coil configuration, to maximize the amplifier's achievable power and improve connection versatility.
7. High magnetic permeability plates and large magnet, ensuring a constant and even magnetic flux, for perfect low frequency control.
8. Butyl rubber gasket and magnet protective cover, provide ideal coupling to the mounting surface, damping basket resonances.

Electro-Acoustic Parameters

D	mm	212
Xmax	mm	9
Re	Ω	2 (parallel)
Fs	Hz	40
Le	mH	1,1
Vas	l	30,6
Mms	g	90
Cms	mm/N	0,18
BL	T·m	7,8
Qts	-	0,66
Qes	-	0,72
Qms	-	7,9
Spl	dB	92

A	264 mm	10.4 in.
B	234 mm	9.21 in.
C	136 mm	5.25 in.
D	119 mm	4.68 in.

