



Tempo Ultra Integra Specifications

Tempo Integra		402	502	602
Nominal Impedance		4 ohm	4 ohm	4 ohm
Power Handling		60W	100W	110W
Max. Transient Power Handling		140W	220W	220W
Sensitivity (2.83V/1M)		85db	89db	90db
Frequency Response		80-22000Hz	55-22000Hz	50-22000Hz
Voice Coil Diameter	Woofer:	32 mm (1.30")	38 mm (1.50")	38 mm (1.50")
	Tweeter:	19 mm (1.00")	25 mm (1.00")	25 mm (1.00")
Voice Coil Wire	Woofer:	Copper	Copper	Copper
	Tweeter:	Copper	Copper	Copper
Magnet System	Woofer:	high-grade ferrite	high-grade ferrite	high-grade ferrite
	Tweeter:	Neodymium	Neodymium	Neodymium
Mounting Depth		57 mm (2.25")	57 mm (2.25")	64 mm (2.52")

Tempo Integra		572	692
Nominal Impedance		4 ohm	4 ohm
Power Handling		100W	140W
Max. Transient Power Handling		220W	250W
Sensitivity (2.83V/1M)		90db	92db
Frequency Response		60-22000Hz	35-22000Hz
Voice Coil Diameter	Woofer:	38 mm (1.50")	38 mm (1.50")
	Tweeter:	25 mm (1.00")	25 mm (1.00")
Voice Coil Wire	Woofer:	Copper	Copper
	Tweeter:	Copper	Copper
Magnet System	Woofer:	high-grade ferrite	high-grade ferrite
	Tweeter:	Neodymium	Neodymium
Mounting Depth		62 mm (2.45")	85 mm (3.35")