



CWRT101-43

**Dual Voice Coil
Subwoofer 25 cm**

Power Handling
400 Watts RMS / 800 Watts Max.

Technical Specifications

Impedance	Zn	2 x 1 Ohms
Voice Coil Diameter	Ø	50 mm
Max. Linear Excursion	Xmax	+/- 12,73 mm
Cone Area	Sd	346,4 cm ²
Moving Mass	Mms	154,58 g
DC Resistance	Re	2 x 1,1 Ohms
Resonance Frequency	Fs	29,9 Hz
Mechanical Q-Factor	Qms	14,19
Electrical Q-Factor	Qes	0,445
Total Q-Factor	Qts	0,432
Equivalent Air Volume	VAS	31,1 L
VC Inductance	Le	3,043 mH
Flux Density	B/L	11,34 N/A
Efficiency 1W/1m	SPL	84,8 dB

Recommended Enclosure

Ported Box	
Vented Volume:	49,6 L
Port Diameter:	147 mm
Port Area:	170 cm ²
Port Length:	50,8 cm
Sound Quality	

Recommended Enclosure

Ported Box	
Vented Volume:	35,4 L
Port Diameter:	132 mm
Port Area:	136 cm ²
Port Length:	50,8 cm

Mechanical Components

- Steel Basket
- Polypropylene Cone
- Santoprene Surround
- Polypropylene Dustcap
- Single Spider
- Polyimide Voice Coil Former

Dimensions & Weight

External Diameter:	271 mm
Mounting Diameter:	232 mm
Mounting Depth:	88 mm
Shipping Weight:	5,8 kg

